

# Identification system with strapping for marker carriers PLIO-M-MARKERS




PLIO®



## • Identification system PLIOSTRAP-8

| Colour | 004    | 010   |
|--------|--------|-------|
|        | yellow | black |



| type        | article number |     |
|-------------|----------------|-----|
| PLIOSTRAP-8 | 0362 8200 ***  | 100 |

**Applications:** system for the identification of cables in the field of lighting, light signals and various other installations of outdoor space supplied at low or high voltage.

### Composition of the PLIOSTRAP-8\* identification system:



- 100 pre-assembled strappings PLIO-8 Lg 280 mm with a loop and 2 locking studs N° 2 PS
- 100 locking studs N° 1 PS
- 100 cable-ties SX 155/30 colour black

\* The identification carriers must be ordered separately.



## • Identification carrier PLIO-M-MARKERS

| type | white             | article number<br>internat. colour | unprinted colour | <br>rings |
|------|-------------------|------------------------------------|------------------|-----------|
| M-60 | 0362 0008 001 *** | 0362 0018 ****                     | 0362 0118 ***    | 1000      |



## • Box

| type      | article number | external dimensions (mm) |       |        | weight<br>g |   |
|-----------|----------------|--------------------------|-------|--------|-------------|---|
|           |                | length                   | width | height |             |   |
| BOX PSC18 | 0370 0910 000  | 240                      | 195   | 43     | 295         | 1 |



C12/4-01



# Identification system

## with marker carriers

### Accessories



PLIO-MARKERS



#### PLIO M-\*\*\*

|                                   |   |              |  |
|-----------------------------------|---|--------------|--|
| <b>Material:</b>                  | PVC   | PE           |  |
| <b>Operating temperatures:</b>    | -20 to +95°C                                      | -50 to +85°C |  |
| <b>Shore hardness:</b>            | 95 ±5 (Shore A)                                   | 44 (Shore D) |  |
| <b>Tensile strength at break:</b> | 20 MPa  | 16 MPa       |  |
| <b>Ultimate elongation:</b>       | 300 %   | 550 %        |  |
| <b>Application:</b>               | for the identification of large cables and tubes. |              |  |




#### • Identification carrier PLIO in PVC coloured for carrier markers M-65 + V-65

| code colour | 001   | 002  | 003   | 004    | 005    | 007 | 010   |
|-------------|-------|------|-------|--------|--------|-----|-------|
|             | white | blue | green | yellow | orange | red | black |

| type      | article number | useful dimensions<br>L x W (mm) | quant. of markers<br>M-65/carrier |     |
|-----------|----------------|---------------------------------|-----------------------------------|-----|
|           |                |                                 |                                   |     |
| M-008 PVC | 0140 0011 ***  | 42 x 9,5                        | 8                                 | 100 |
| M-012 PVC | 0140 0012 ***  | 62 x 9,5                        | 12                                | 100 |
| M-024 PVC | 0140 0013 ***  | 122 x 9,5                       | 24                                | 100 |

Example for order:

| code group | detail article | code colour |
|------------|----------------|-------------|
| 0140       | 0011           | 003         |
| 0140       | 0012           | 003         |
| 0140       | 0013           | 003         |



#### • Identification carrier PLIO in PE natural halogene free for carrier markers M-65 + V-65

| type     | article number | useful dimensions<br>L x W (mm) | quant. of markers<br>M-65/carrier |     |
|----------|----------------|---------------------------------|-----------------------------------|-----|
|          |                |                                 |                                   |     |
| M-008 PE | 0140 0001 018  | 42 x 9,5                        | 8                                 | 100 |
| M-012 PE | 0140 0002 018  | 62 x 9,5                        | 12                                | 100 |
| M-024 PE | 0140 0003 018  | 122 x 9,5                       | 24                                | 100 |



#### • Identification carrier PLIO in PE natural halogene free for carrier markers M-40 - V-40

| type        | article number | useful dimensions<br>L x W (mm) | quant. of markers<br>M-40/barrette |     |
|-------------|----------------|---------------------------------|------------------------------------|-----|
|             |                |                                 |                                    |     |
| M-008/40 PE | 0140 0004 018  | 48,5 x 4,7                      | 8                                  | 100 |



#### • Cable strapping PLIO in flexible PVC for PLIO-MARKERS carriers

| type      | article number | width (mm) | colours |    |
|-----------|----------------|------------|---------|----|
|           |                |            |         |    |
| PLIO 8 mm | 0811 0001 010  | 8          | black   | 50 |
| PLIO 8 mm | 0811 0001 013  | 8          | grey    | 50 |
| PLIO 8 mm | 0811 0001 011  | 8          | natural | 50 |



#### • PLIO fixing studs for PLIO cable strapping

| type   | article number | material               |     |
|--------|----------------|------------------------|-----|
|        |                |                        |     |
| n°1 PS | 0103 0001 010  | polystyrene choc black | 500 |
| n°1 PA | 0104 0009 010  | polyamide black        | 500 |
| n°1 PE | 0130 0001 018  | polyethylene natural   | 500 |



#### • Stud application tool PLIO


| type | article number | length (mm) |   |
|------|----------------|-------------|---|
|      |                |             |   |
| 2061 | 0408 0001 000  | 140         | 1 |



B1/7-01



B7/3-05



C12/1-01 maxi width 4,7 mm



# Markers PLIO® M-65 standard to identify PLIO carriers



PLIO-M-MARKERS



## PLIO M-65

**Material:** flexible PVC  
**Operating temperatures:** -20 to +90°C  
**Hardness Shore A:** 80 ± 3  
**Tensile strength at break:** 18 MPa  
**Ultimate elongation:** 250 %  
**Dielectric strength:** > 20 kV/mm  
**Flame resistance:** V0 UL94  
**Pack:** reels with 500 markers  
**Application:** to identify PLIO carriers.



Example for order:

| code group | detail article | code colour | code legend |
|------------|----------------|-------------|-------------|
| 03620070   |                | x x x x x x |             |

|   |   |   |   |   |   |   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| F | 0 | 3 | 6 | 2 | 0 | 0 | 7 | 0 | 0 | 0 | 1 | F |
|---|---|---|---|---|---|---|---|---|---|---|---|---|

|   |   |   |   |   |   |   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 5 | 0 | 3 | 6 | 2 | 0 | 0 | 7 | 0 | 0 | 0 | 4 | 5 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|




6.

### code colour

|       |       |     |        |        |       |      |        |      |       |      |
|-------|-------|-----|--------|--------|-------|------|--------|------|-------|------|
| 010   | 006   | 007 | 005    | 004    | 003   | 002  | 008    | 013  | 001   | 015  |
| black | brown | red | orange | yellow | green | blue | violet | grey | white | pink |

### code legends

|    |    |                   |
|----|----|-------------------|
| A  | A  | 0362 0070 *** A   |
| B  | B  | 0362 0070 *** B   |
| C  | C  | 0362 0070 *** C   |
| D  | D  | 0362 0070 *** D   |
| E  | E  | 0362 0070 *** E   |
| F  | F  | 0362 0070 *** F   |
| G  | G  | 0362 0070 *** G   |
| H  | H  | 0362 0070 *** H   |
| I  | I  | 0362 0070 *** I   |
| J  | J  | 0362 0070 *** J   |
| K  | K  | 0362 0070 *** K   |
| L  | L  | 0362 0070 *** L   |
| M  | M  | 0362 0070 *** M   |
| N  | N  | 0362 0070 *** N   |
| O  | O  | 0362 0070 *** O   |
| P  | P  | 0362 0070 *** P   |
| Q  | Q  | 0362 0070 *** Q   |
| R  | R  | 0362 0070 *** R   |
| S  | S  | 0362 0070 *** S   |
| T  | T  | 0362 0070 *** T   |
| U  | U  | 0362 0070 *** U   |
| V  | V  | 0362 0070 *** V   |
| W  | W  | 0362 0070 *** W   |
| X  | X  | 0362 0070 *** X   |
| Y  | Y  | 0362 0070 *** Y   |
| Z  | Z  | 0362 0070 *** Z   |
| 0  | 0  | 0362 0070 *** 0   |
| 1  | 1  | 0362 0070 *** 1   |
| 2  | 2  | 0362 0070 *** 2   |
| 3  | 3  | 0362 0070 *** 3   |
| 4  | 4  | 0362 0070 *** 4   |
| 5  | 5  | 0362 0070 *** 5   |
| 6. | 6. | 0362 0070 *** 6   |
| 7  | 7  | 0362 0070 *** 7   |
| 8  | 8  | 0362 0070 *** 8   |
| 9. | 9. | 0362 0070 *** 9   |
| +  | +  | 0362 0070 *** +   |
| -  | -  | 0362 0070 *** -   |
| .  | .  | 0362 0070 *** .   |
| =  | =  | 0362 0070 *** =   |
| *  | *  | 0362 0070 *** *   |
| /  | /  | 0362 0070 *** /   |
| ⊥  | ⊥  | 0362 0070 *** TER |
| ~  | ~  | 0362 0070 *** ALT |
| Ω  | Ω  | 0362 0070 *** OHM |
| +  |    | 0362 0070 007 +   |
| -  |    | 0362 0070 002 -   |
|    |    | 0362 0070 010 0   |
|    |    | 0362 0070 006 1   |
|    |    | 0362 0070 007 2   |
|    |    | 0362 0070 005 3   |
|    |    | 0362 0070 004 4   |
|    |    | 0362 0070 003 5   |
|    |    | 0362 0070 002 6   |
|    |    | 0362 0070 008 7   |
|    |    | 0362 0070 013 8   |
|    |    | 0362 0070 001 9   |
|    |    | 0362 0070 010     |
|    |    | 0362 0070 006     |
|    |    | 0362 0070 007     |
|    |    | 0362 0070 005     |
|    |    | 0362 0070 004     |
|    |    | 0362 0070 003     |
|    |    | 0362 0070 002     |
|    |    | 0362 0070 008     |
|    |    | 0362 0070 013     |
|    |    | 0362 0070 001     |
|    |    | 0362 0070 015     |



reel with 500 markers

B7/4-05



**Identification system M2**  
**with marker carriers M2**  
**PLIO-M-MARKERS**




PLIO-MARKERS




**PLIO M-\*\*\*-M2**

**Material:** PVC  
**Operating temperatures:** -20 to +95°C  
**Colour:** yellow (white upon request)  
**Hardness Shore A:** 95 ±5 (Shore A)  
**Tensile strength at break:** 20 MPa  
**Ultimate elongation:** 300 %  
**Specification:** V0 UL94  
M2 CSTB  
**Application:** for the identification of large cables and tubes.




**• Identification carrier PLIO-M2 yellow virtual non-flame grade for M-65-M2 marker carriers**

| type     | artide number | useful dimensions<br>L x W (mm) | quant. of markers<br>M-65 per carrier |  |
|----------|---------------|---------------------------------|---------------------------------------|---|
| M-008-M2 | 0369 0011 004 | 42 x 9,5                        | 8                                     | 100   |
| M-012-M2 | 0369 0012 004 | 62 x 9,5                        | 12                                    | 100   |
| M-024-M2 | 0369 0013 004 | 122 x 9,5                       | 24                                    | 100   |




**• Cable strapping PLIO-M2 in PVC, yellow virtual non-flame grade for PLIO-MARKERS M2 marker carriers**

| type      | artide number | width (mm) | thickness (mm) |  m |
|-----------|---------------|------------|----------------|---|
| PLIO 8-M2 | 0369 0021 004 | 8          | 1              | 50  |



**• Fixing stud PLIO PA-V2 for cable strapping PLIO**

| type       | artide number | material           |  |
|------------|---------------|--------------------|---|
| n° 1 PA-V2 | 0369 0031 000 | polyamide V2 white | 500   |




 B1/7-01



B7/3-05



C12/23-01 maxi width 4,7 mm



# Markers PLIO® M-65 M2 on reels to identify carriers PLIO-M2




PLIO-M-MARKERS



## PLIO M-65 M2

**Material:** flexible PVC  
**Operating temperatures:** -20 to +90°C  
**Hardness Shore A:** 80 ±5  
**Tensile strength at break:** 18 MPa  
**Ultimate elongation:** 280 %  
**Dielectric strength:** > 20 kV/mm  
**Flame resistance:** V0 UL94  
M2 CSTB  
**Pack:** reel with 500 markers  
**Application:** for a use on PLIO M2 carriers.



Example for order:

| code group | detail article | code colour | code legend |
|------------|----------------|-------------|-------------|
| 0369       | 0001           | X           | X           |


|   |              |
|---|--------------|
| A | 03690001004A |
| + | 03690001001+ |



6.

| code colour | 010   | 006   | 007 | 005    | 004    | 003   | 002  | 008    | 013  | 001   | 015  |
|-------------|-------|-------|-----|--------|--------|-------|------|--------|------|-------|------|
|             | black | brown | red | orange | yellow | green | blue | purple | grey | white | pink |

| code legends | A               | B               | C               | D               | E               | F               | G               | H               | I               | J               | K               | L               | M               | N               | O               | P               | Q               | R               | S               | T               | U               | V               | W               | X               | Y               | Z               | 0               | 1               | 2               | 3               | 4               | 5               | 6               | 7               | 8               | 9               | +               | -               | .               | =               | *               | /               | TER               | ALT               | OHM               |
|--------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-------------------|-------------------|-------------------|
|              | A               | B               | C               | D               | E               | F               | G               | H               | I               | J               | K               | L               | M               | N               | O               | P               | Q               | R               | S               | T               | U               | V               | W               | X               | Y               | Z               | 0               | 1               | 2               | 3               | 4               | 5               | 6               | 7               | 8               | 9               | +               | -               | .               | =               | *               | /               | TER               | ALT               | OHM               |
|              | 0369 0001 *** A | 0369 0001 *** B | 0369 0001 *** C | 0369 0001 *** D | 0369 0001 *** E | 0369 0001 *** F | 0369 0001 *** G | 0369 0001 *** H | 0369 0001 *** I | 0369 0001 *** J | 0369 0001 *** K | 0369 0001 *** L | 0369 0001 *** M | 0369 0001 *** N | 0369 0001 *** O | 0369 0001 *** P | 0369 0001 *** Q | 0369 0001 *** R | 0369 0001 *** S | 0369 0001 *** T | 0369 0001 *** U | 0369 0001 *** V | 0369 0001 *** W | 0369 0001 *** X | 0369 0001 *** Y | 0369 0001 *** Z | 0369 0001 *** 0 | 0369 0001 *** 1 | 0369 0001 *** 2 | 0369 0001 *** 3 | 0369 0001 *** 4 | 0369 0001 *** 5 | 0369 0001 *** 6 | 0369 0001 *** 7 | 0369 0001 *** 8 | 0369 0001 *** 9 | 0369 0001 *** + | 0369 0001 *** - | 0369 0001 *** . | 0369 0001 *** = | 0369 0001 *** * | 0369 0001 *** / | 0369 0001 *** TER | 0369 0001 *** ALT | 0369 0001 *** OHM |



reel with 500 markers

B7/4-05



# Identification system with marker carriers

flame resistant, halogene free




PLIO-MARKERS



## Marker carriers PLIO M-\*\*\* PP

**Material:** PP (polypropylene)  
**Colours:** white - black  
**Operating temperatures:** -20 to +90°C  
**Ultimate elongation:** 22 MPa  
**Flame resistance:** V0 UL94  
**Application:** identification in halogen free applications requiring high fire resistance (ex: tunnel, rolling material, rail ...).



| type     | article number |               | useful dimensions<br>L x B (mm) | quant. markers<br>M-65/carrier |     |
|----------|----------------|---------------|---------------------------------|--------------------------------|-----|
|          | white          | black         |                                 |                                |     |
| M-008 PP | 0140 0201 001  | 0140 0201 010 | 42 x 9,5                        | 8                              | 100 |
| M-012 PP | 0140 0202 001  | 0140 0202 010 | 62 x 9,5                        | 12                             | 100 |
| M-024 PP | 0140 0203 001  | 0140 0203 010 | 122 x 9,5                       | 24                             | 100 |



## Markers PLIO M-65 TPU

**Material:** TPU (thermoplastic polyurethane)  
**Colours:** white - yellow  
**Operating temperatures:** -30 to +90°C  
**Hardness Shore A:** 77 ±5  
**Tensile strength at break:** 30 MPa  
**Ultimate elongation:** 600%  
**Flame resistance:** V0 UL94  
**Pack:** reel with 500 markers




**Application:** with our PP marker carriers or directly on cables with Ø 4,2 to 6,6 mm. In halogen free applications requiring a high flame resistance (ex: tunnel, rolling material, rail ...).

Ejemplo para pedido:

**Code Colour**



| code group | detail article | code colour | code legend     |
|------------|----------------|-------------|-----------------|
| 0368       | 0001           | 1           | x x x x x x x x |





**code legends**

|   |   |                 |   |   |                 |   |    |                 |   |   |                   |
|---|---|-----------------|---|---|-----------------|---|----|-----------------|---|---|-------------------|
| A | A | 0368 0001 *** A | N | N | 0368 0001 *** N | 0 | 0  | 0368 0001 *** 0 | + | + | 0368 0001 *** +   |
| B | B | 0368 0001 *** B | O | O | 0368 0001 *** O | 1 | 1  | 0368 0001 *** 1 | - | - | 0368 0001 *** -   |
| C | C | 0368 0001 *** C | P | P | 0368 0001 *** P | 2 | 2  | 0368 0001 *** 2 | . | . | 0368 0001 *** .   |
| D | D | 0368 0001 *** D | Q | Q | 0368 0001 *** Q | 3 | 3  | 0368 0001 *** 3 | = | = | 0368 0001 *** =   |
| E | E | 0368 0001 *** E | R | R | 0368 0001 *** R | 4 | 4  | 0368 0001 *** 4 | * | * | 0368 0001 *** *   |
| F | F | 0368 0001 *** F | S | S | 0368 0001 *** S | 5 | 5  | 0368 0001 *** 5 | / | / | 0368 0001 *** /   |
| G | G | 0368 0001 *** G | T | T | 0368 0001 *** T | 6 | 6. | 0368 0001 *** 6 | ⊥ | ⊥ | 0368 0001 *** TER |
| H | H | 0368 0001 *** H | U | U | 0368 0001 *** U | 7 | 7  | 0368 0001 *** 7 | ~ | ~ | 0368 0001 *** ALT |
| I | I | 0368 0001 *** I | V | V | 0368 0001 *** V | 8 | 8  | 0368 0001 *** 8 | Ω | Ω | 0368 0001 *** OHM |
| J | J | 0368 0001 *** J | W | W | 0368 0001 *** W | 9 | 9. | 0368 0001 *** 9 |   |   |                   |
| K | K | 0368 0001 *** K | X | X | 0368 0001 *** X |   |    |                 |   |   |                   |
| L | L | 0368 0001 *** L | Y | Y | 0368 0001 *** Y |   |    |                 |   |   |                   |
| M | M | 0368 0001 *** M | Z | Z | 0368 0001 *** Z |   |    |                 |   |   |                   |

Other sizes of markers  
 PLIO-M-MARKERS TPU on request.

reel with 500 markers



C12/23-01 Cable-tie SL V0 (AF) halogene free, maxi. width 4,7 mm



# Identification system sensitive to metal detectors



PLIO-M-MARKERS



## PLIO PP MDE

**Material:** PP with metal particles  
**Colour:** metal blue  
**Operating temperatures:** -20 to +70°C  
**Chemical resistance:** good resistance to acids, bases and detergents.  
**Specifications:** halogen free  
 adapted to the success of a HACCP\* processes.

**Application:** The presence of metal particles in the identification carriers or markers allows easy detection thanks to any metal detector. This identification system is thus used in electrical equipment boxes or chains of production in food and pharmaceutical industries to limit the risks of product contamination.



\* HACCP : Hazard Analysis Critical Control Point

### ● Identification carrier PLIO M-\*\*\* PP MDE

| type         | art. no.      | useful dimensions<br>L x l (mm) | quant. of markers<br>M-65/carrier |     |
|--------------|---------------|---------------------------------|-----------------------------------|-----|
| M-008 PP MDE | 0140 1001 093 | 42 x 9,5                        | 8                                 | 100 |
| M-012 PP MDE | 0140 1002 093 | 62 x 9,5                        | 12                                | 100 |
| M-024 PP MDE | 0140 1003 093 | 122 x 9,5                       | 24                                | 100 |




### ● Markers PLIO M-65 PP MDE

for identification carrier PLIO M-\*\*\* PP MDE

| type           | artide number   |     |
|----------------|-----------------|-----|
| M-65 PP MDE    | 0368 0100 093 * | 500 |
| M-65 PP MDE EG | 0368 0200 093 * | 100 |



|   |                 |   |                 |   |                 |
|---|-----------------|---|-----------------|---|-----------------|
| A | 0368 xxxx 093 A | N | 0368 xxxx 093 N | 0 | 0368 xxxx 093 0 |
| B | 0368 xxxx 093 B | O | 0368 xxxx 093 O | 1 | 0368 xxxx 093 1 |
| C | 0368 xxxx 093 C | P | 0368 xxxx 093 P | 2 | 0368 xxxx 093 2 |
| D | 0368 xxxx 093 D | Q | 0368 xxxx 093 Q | 3 | 0368 xxxx 093 3 |
| E | 0368 xxxx 093 E | R | 0368 xxxx 093 R | 4 | 0368 xxxx 093 4 |
| F | 0368 xxxx 093 F | S | 0368 xxxx 093 S | 5 | 0368 xxxx 093 5 |
| G | 0368 xxxx 093 G | T | 0368 xxxx 093 T | 6 | 0368 xxxx 093 6 |
| H | 0368 xxxx 093 H | U | 0368 xxxx 093 U | 7 | 0368 xxxx 093 7 |
| I | 0368 xxxx 093 I | V | 0368 xxxx 093 V | 8 | 0368 xxxx 093 8 |
| J | 0368 xxxx 093 J | W | 0368 xxxx 093 W | 9 | 0368 xxxx 093 9 |
| K | 0368 xxxx 093 K | X | 0368 xxxx 093 X | - | 0368 xxxx 093 - |
| L | 0368 xxxx 093 L | Y | 0368 xxxx 093 Y | / | 0368 xxxx 093 / |
| M | 0368 xxxx 093 M | Z | 0368 xxxx 093 Z |   |                 |



reel with 500 markers

bag with 100 markers

C12/3-01 - Cable tie SL MDE, maxi. width 4,7 mm



A5/1-03 - Spiral tubing PLIOSPIRE MDE





[www.klinkmann.com](http://www.klinkmann.com)

**HELSINKI**

tel. +358 9 540 4940  
info@klinkmann.fi

**ST. PETERSBURG**

tel. +7 812 327 3752  
klinkmann@klinkmann.spb.ru

**MOSCOW**

tel. +7 495 641 1616  
moscow@klinkmann.spb.ru

**YEKATERINBURG**

tel. +7 343 287 19 19  
yekaterinburg@klinkmann.spb.ru

**SAMARA**

tel. +7 846 273 95 85  
samara@klinkmann.spb.ru

**UFA**

tel. +7 347 293 70 04  
klinkmann@klinkmann.ru

**KIEV**

tel. +38 044 495 33 40  
klinkmann@klinkmann.kiev.ua

**KAZAKHSTAN**

tel. +77779994825  
sales@klinkmann.kz

**MINSK**

tel. +375 17 200 0876  
minsk@klinkmann.com

**RIGA**

tel. +371 6738 1617  
info@klinkmann.lv

**VILNIUS**

tel. +370 5 215 1646  
info@klinkmann.lt

**TALLINN**

tel. +372 668 4500  
info@klinkmann.ee