

## MAS0606030R5 Wall mounted, 600x600x300

The mild steel single door wall mounted enclosure range, MAS, with a IP 66 protection degree, is available off the shelf in many different sizes. This enclosure range is well suited for many different applications. The risk for component failure, and with that unnecessary downtime, is eliminated as water and dust are prevented from entering the enclosure.

### Feature:

IP 66 TYPE 4, 12, 13 IK 10

CE Declaration of Conformity  
DNV-GL GOST Kema Keur -  
DEKRA Lloyd's Register Russian  
Maritime Register of Shipping  
cULus\_UL Listed



Item no.: MAS0606030R5  
EAN no.: 8713574128262

### CHARACTERISTICS

Note	With mounting plate
Height	600 mm
Width	600 mm
Depth	300 mm
Mounting Plate Height	570 mm
Mounting Plate Width	550 mm
Max. enclosure useful depth	282 mm
Gland Plate	510 x 96 mm
Opening Size Type	4
No. of Gland Plate Openings	1
No Locks	2
Weight (kg)	24.55

### Technical data

#### Material:

Body: 1.2 mm mild steel for enclosures with a depth of 155 mm / 1.4 mm for enclosures with a depth of 210 or 260 mm / 1.5 mm for enclosures with a depth of 300 or 400 mm, or if a height or width is 1000 mm or greater. Gland plate: 1.4 mm mild steel. Door: 1.2 mm mild steel / 1.5 mm for enclosures with a height or width of 500 mm or greater / 2 mm for enclosures with a height or width of 800 mm or greater. Mounting plate: 2 mm galvanized steel.

#### Body:

Folded and seam welded. Four 8.5 mm diameter holes for wall fixing, pressed out in 20.4 mm diameter x 2 mm depressions, to allow air circulation around the rear part of the enclosure.

#### Door:

Surface mounted with 130° opening. Concealed removable hinges with captive pin. Hinges can be mounted to allow left or right hand opening. Inner M6 welded studs to mount door profiles MMDP. Sealing is ensured by an injected one piece polyurethane gasket.

#### Lock:

Customized lock with double-bit for easy opening of the door. Double-bit 3 mm insert and 90° movement. 1000 mm high enclosures and above have espagnolette three point locking. Other inserts are available as an accessory.

#### Mounting plate:

The mounting plate is marked vertically at 10 mm intervals, for easy horizontal positioning of equipment. On the top and bottom there are holes to facilitate cable fixing. Fixed onto M8 press welded studs to the rear of the enclosure. All sides, from 800 mm and above, are strengthened by folded edges. By using the AMG accessory, the mounting plate position can be adjusted to any depth.

#### Gland Plate Opening:

Situated at the far rear of the enclosure, to make cabling onto the mounting plate easier.

#### Protection:

Complies with IP 66 | TYPE 4, 12, 13 | IK 10. For outdoor installation, the use of a rain hood ARF and 100% polyester paint coating is recommended. The corrosion resistance must be taken into consideration.

- Finish:** RAL 7035 structured powder coating.
- Delivery:** Enclosure with door. For height 600 mm and above, two door mounting profiles. Gland plate(s) with gasket(s), plastic double-bit 3 mm key, and mounting accessories. Metallic key, for height 1000 mm and above. Earthing facilities.

## Features

- Feature:** Mild steel single door wall mounted enclosure, available in a wide range of sizes with a high IP 66 protection degree.
- Advantage:** Customers can choose enclosures that meet their size requirements, off the shelf. The installed components inside the enclosure will be safe and secure due to the high protection degree
- Benefit:** Customers can receive enclosures with a short delivery time, that match their size requirements. This will also remove any extra costs due to oversizing. Component failure and unnecessary downtime is avoided as water and dust are prevented from entering the enclosure.