



## PROFIBUS connector, 90° screw terminal

without PG

- Metalized housing
- No parts that can be lost
- Integrated switchable terminating resistor
- 90° cable outlet
- Proven screw terminal
- The PROFIBUS connectors are also available in packs of 10 or 50
- The maximum ambient temperature for UL is +60 °C.

The PROFIBUS connector 90° is equipped with a proven and reliable screw terminal. It is quickly mounted and has integrated, connectable terminating resistors. For improved EMC compatibility, the housing of the plug is metalized. The PROFIBUS connector works in the extended ambient temperature range of -25 °C to +85 °C

### Technical specifications

<b>General information</b>	
Order number	700-972-0BA12
Article name	PROFIBUS connector, 90° , screw terminal, without PG
Scope of delivery	PROFIBUS connector, installation instructions
Dimensions (DxWxH)	64 x 40 x 17 mm
Weight	Approx. 40 g
Cable outlet	Vertical cable outlet, suitable for FastConnect stripping tool
<b>PROFIBUS interface</b>	
Number	1
Transmission rate	max. 12 Mbps
Connection	SUB-D connector, 9-pin
Terminating resistor	Resistor combination integrated and switchable using slide switch
PG connection socket	No
PROFIBUS bus cable	60/75 °C copper cable up to 1.0 mm <sup>2</sup>
<b>Connector</b>	
Connector type	terminal strips
Number	4
Maximum outside diameter	8.0 mm
Voltage supply	+ 4.75 ... + 5.25 V DC (must come from the device)
Current draw	Max. 12.5 mA
<b>Ambient conditions</b>	
Ambient temperature	-25 °C ... +85 °C (The maximum ambient temperature for UL is +60 °C.)
Transport and storage temperature	-25 °C ... +85 °C
Relative air humidity	70 % at +25 °C

Pollution degree	2
Protection rating	IP20
Certifications	CE, UL
<b>CE</b>	
RoHS	Yes
REACH	Yes